



RPM	MODELLO MODEL	PORTATA FLOW		PRESSIONE PRESSURE		POTENZA POWER		PESO WEIGHT	
		l/min	GPM	bar	PSI	HP	kW		
1450	MC 13/20 S	13.0	3.4	200	2900	6.7	4.9	9.3	S = Albero Maschio 24 mm S = Male Shaft 24 mm
	MC 13/20 I	13.0	3.4	200	2900	6.7	4.9	10.0	
	MC 15/15 S	15.0	4.0	150	2175	5.8	4.2	9.3	I = Albero Cavo 28 mm (con Flangia M02) I = Hollow Shaft 28 mm (with Flange M02)
	MC 15/20 S	15.0	4.0	200	2900	7.7	5.7	9.3	
	MC 15/20 I	15.0	4.0	200	2900	7.7	5.7	10.0	
	MC 18/20 S	18.0	4.8	200	2900	9.2	6.8	9.3	
	MC 20/15 S	20.0	5.3	150	2175	7.7	5.7	9.3	
	MC 20/20 S	20.0	5.3	200	2900	10.3	7.5	9.3	
1750	MD 4.0/20 S	15.0	4.0	140	2030	5.4	4.0	9.3	S = Albero Maschio 24 mm S = Male Shaft 24 mm
	MD 4.0/20 U	15.0	4.0	140	2030	5.4	4.0	10.5	
	MD 4.0/30 S	15.0	4.0	200	2900	7.7	5.7	9.3	U = Albero Cavo 1"1/8 (con Flangia M03) U = Hollow Shaft 1"1/8 (with Flange M03)
	MD 4.0/30 U	15.0	4.0	200	2900	7.7	5.7	10.5	
	MD 5.0/30 S	19.0	5.0	200	2900	9.7	7.2	9.3	
	MD 5.0/30 U	19.0	5.0	200	2900	9.7	7.2	10.5	
2800	ME 15/20 S	15.0	4.0	200	2900	7.7	5.7	9.3	S = Albero Maschio 24 mm/Male Shaft 24 mm
3400	ML 3.5/30 W	13.2	3.5	200	2900	6.7	4.9	10.4	W = Albero Cavo 1" (con Flangia M01) W = Hollow Shaft 1" (with Flange M01)
	ML 4.0/30 W	15.0	4.0	200	2900	7.7	5.7	10.4	
	ML 5.0/30 W	19.0	5.0	200	2900	9.7	7.2	10.4	

Per le dimensioni d'ingombro vedi pagina a fianco.  
For overall dimensions see page beside.

Vedi pag. 38-39 - See pag. 38-39